



PE.PEX Series Jaw Crusher



Leading crushing and screening equipment manufacturer in China

中国领先的破碎筛分设备制造商

郑州一帆机械设备有限公司(由山德技术(北京)有限公司控股),是中国知名的破碎筛分设备制造商。我们为客户提供全系列破碎筛分设备,包括 液压圆锥破碎机、颚式破碎机、反击式破碎机、立式冲击破碎机(制砂机)、移动式破碎站和振动筛,我们不仅为客户提供高性价比的产品,还提供一流的服务支持及解决方案。



















郑州一帆机械设备有限公司

ZHENGZHOU YIFAN MACHINERY CO.,LTD 服务热线: 400-665-6688 0371-64627000 64989888

网址:www.yfmac.com 地址:中国郑州荥阳开发区郑源路

PE.PEX系列**颚式破碎机**

PE. PEX Series Jaw Crusher



PE、PEX系列颚式破碎机破碎比大、产品粒度 均匀。用于破碎抗压强度不超过320Mpa的物料。 PE系列用于粗碎, PEX系列用于中、细碎。

PE,PEX Series Single Toggle Jaw Crusher has the features of great crushing ratio, uniform sizes of product. It can be used to crush material with compressive resistance not more than 320 Mpa.

PE series is used in primary crushing, PEX series is used in secondary crushing and fine crushing.

特点及优势:

- ◎结构简单、工作可靠
- ◎维修方便、运行费用经济

Features and Benefits:

- OSimple structure and reliable operation
- OConvenient maintenance and low operation cost

技术参数 Technical Data

型号 Model	进料口尺寸 Size of Feed Opening(mm)	最大进料粒度 Max Feed Size(mm)	排料口调整范围 Discharge Range Opening(mm)	处理能力 Capacity(m³/h)	电机功率 Motor Power(kw)	重量 Weight(t)
PE-400×600	400×600	340	40-100	10-40	30	6.1
PE-500 × 750	500 × 750	425	50-100	25-60	55	10.5
PE-600×900	600×900	500	65–180	30-85	55–75	14.8
PE-750×1060	750 × 1060	630	80–180	72–150	90–110	28
PE-870×1060	870×1060	750	170–270	145–235	90–110	28.45
PE-900×1200	900 × 1200	780	100–200	100-240	110–132	45.2
PE-1000 × 1200	1000 × 1200	850	200–280	190–275	110–132	45.7
PE-1200 × 1500	1200 × 1500	1020	150–300	250-500	200	89
PE-1500 × 1800	1500 × 1800	1200	220–350	430-1000	355	122
PEX-150 × 750	150 × 750	120	10–40	5–16	15	2.53
PEX-250 × 1000	250 × 1000	210	25-60	10–30	30–37	6.5
PEX-250 × 1200	250 × 1200	210	25-60	13–35	37	7.7
PEX-300 × 1300	300×1300	250	20-90	13-53	75	11.4


注: 上述生产能力是在破碎中硬及以下物料且堆积密度为1.6×10³kg/m³时开路循环生产中的总吨数。生产能力与破碎物料的物料性能、给料方式、进料粒度及其组成有关。

Note: The capacity is total tons per hour passing through crusher at open circuit when crushing medium and below hardness material and bulk density with 1.6x10³kg/m³. Capacities are relative to physical character and type of feeding, feeding size and composition and so on.


PE. PEX Series Jaw Crusher


结构图 Structural Drawing

- 1. 机架 Frame
- 2. 固定颚板 Fixed Jaw plate
- 3. 活动颚板 Movable Jaw Plate
- 4. 动颚 Movable Jaw
- 5. 偏心轴 Eccentric Shaft
- 6. 肘板 Toggle
- 7. 调整板 Adjusting Toggle Seat



外形尺寸 Overall Dimensions





外形尺寸(mm): Overall Dimensions

					Carlo and Carlo Colon		
型号 Model	А	В	С	D	E	F	G
PE-400 × 600	1710	1680	1640	1040	1125	965	285
PE-500 × 750	2190	1925	1870	1260	1200	1370	435
PE-600 × 900	2510	1875	2300	1400	1505	1640	540
PE-750 × 1060	2910	2585	2600	1720	1945	2030	666
PE-870 × 1060	3030	2585	2600	1720	1945	2080	666
PE-900 × 1200	3530	3000	3035	1825	2290	2255	830
PE-1000 × 1200	3630	3000	3035	1825	2290	2355	830
PE-1200 × 1500	4620	3190	3555	2180	2410	3040	1105
PE-1500 × 1800	5160	3680	4250	2500	2610	3540	1210
PEX-150 × 750	1145	1565	1040	1155	470	590	195
PEX-250 × 1000	1795	1995	1380	1460	850	935	360
PEX-250 × 1200	1805	2210	1430	1625	850	905	360
PEX-300 × 1300	2135	2325	1725	1780	1020	1170	435

注: 上述生产能力是在破碎中硬及以下物料且堆积密度为1.6×10³kg/m³时开路循环生产中的总吨数。生产能力与破碎物料的物料性能、给料方式、进料粒度及其组成有关。

Note: The capacity is total tons per hour passing through crusher at open circuit when crushing medium and below hardness material and bulk density with 1.6x10³kg/m³. Capacities are relative to physical character and type of feeding, feeding size and composition and so on.



总公司: 山德技术(北京)有限公司 SHANDE TECHNOLOGY (BEIJING) CO., LTD.

郑州一帆机械设备有限公司

地址: 中国郑州市荥阳开发区郑源路 邮编: 450100

电话: 0371-6462 7000 6462 6911

传真: 0371-6460 6468

免费咨询电话: 400-665-6688 网址: www.yfmac.com

E-mail: yifan@yfmac.com

ZHENGZHOU YIFAN MACHINERY CO., LTD.

Add: Zhengyuan Rd, Xingyang, Zhengzhou Henan 450100, China

Tel:+86 371 64628852 Fax:+86 371 64628872

Website: www.yfcrusher.com E-mail: sales@yfmac.com

